

MODULAR SIGNAL MANAGEMENT SYSTEM - SABRES50

FEATURES

- High density - Can hold (2) 8-output modules
- All modules are front loading - dedicated rear connector plate for each module
- Versatile frame houses audio/video, analog/digital modules - all at the same time
- Optional redundant supply and control capabilities
- Sleek new design easily integrates into all video and audio environments



SPECIFICATIONS

General

Module Capacity 2 per frame

Mechanical

Temp. Range 0° to 50° C
Cooling Fans Optional
Ventilation Inlet Front panel

Power

AC Input Range 90 - 264VAC
Frequency Range 47 - 64 Hz
Capacity 15W
P.S. Redundancy Hot-swappable
Output/Module Voltage 24VDC
Output Current (max.) 500MA

Control (option)

Connectors 9-pin D-sub, BNC

Prices and specifications are subject to change without notice

MODULES**ANALOG AUDIO DA'S**

1x8 balanced audio DA, 1 slot	SADA8P
1x8 unbalanced audio DA, 1 slot	SADA8R
1X4 balanced audio DA, 1 slot	SADA4P
1X4 unbalanced audio DA, 1 slot	SADA4R
1x16 balanced audio DA, 2 slots	SADAX8P
1x16 unbalanced audio DA, 2 slots	SADAX8R
Dual 1X3 balanced audio DA, 1 slot	SADA2X3P

ANALOG VIDEO DA'S

1x8 analog video DA, looping input, 50 MHZ BW, 1 slot	SVDA8
1x7 looping input analog video DA, 50MHZ BW, 1 slot	SVDA7L
1x8 analog video DA, Eq. to 300 meters, looping input, 50 MHZ BW, 1 slot	SVDQ8
1X4 analog video DA, 50MHZ BW, 1 slot	SVDA4
1X4 analog video DA, EQ to 300 meters, 50 MHZ BW, 1 slot	SVDQ4
Dual 1X3 analog video DA, differential input, 30 MHZ BW, 1 slot	SVDA2X3
Triple 1X2 analog video DA, differential input, 30 MHZ BW, 1 slot	SVDA3X2

DIGITAL AUDIO DA'S

1x4 digital audio DA, balanced AES-3, 110 ohm, 1 slot	SEDA4P
1x4 digital audio DA, unbalanced AES-3ID, 75 ohm, 1 slot	SEDA4B
1x8 digital audio DA, balanced AES-3, 110 ohm, 1 slot	SEDA8P
1x8 digital audio DA, unbalanced AES-3ID, 75 ohm, 1 slot	SEDA8B

DIGITAL VIDEO ASI/SDI DA'S

1x8 digital video DA, Eq. to 300 meters, 1 slot	SSDA8
1x4 digital video DA, EQ to 300 meters, 1 slot	SSDA4
1x8 digital video ASI/SDI DA, Eq. to 300 meters, w/ reclocking, 1 slot	SSDA8R
Dual 1x3 digital video ASI/SDI DA, Eq. to 300 meters, 1 slot	SSDA2X3
Dual 1x3 digital video ASI/SDI DA, Eq. to 300 meters, w/ reclocking, 1 slot	SSDA2X3R

DIGITAL VIDEO HD AND SDI DA'S

1x4 digital video DA, equalizing and reclocking, 1 slot	SHSDA4
1x8 digital video DA, equalizing and reclocking, 1 slot	SHSDA8
Dual 1X3 HD & SDI digital video DA, EQ, & reclocking, 1 slot	SHSDA2X3

CONVERTERS

CONVERTER, 4:2:2 SDI TO ANALOG, 10 Bit, with AES de-Embedder (1 slot) 1SDI in, 1 SDI out, 2 AES out or 2 composite out (jumper selectable), 1 composite video out, 4 analog audio out	SDAC-3164
CONVERTER, 4:2:2 SDI TO ANALOG, 10 Bit, with AES de-Embedder, (1 slot) 1SDI in, 1 SDI out, 2 AES out or 2 composite out (jumper selectable), 1 composite video out, 4 analog audio out, 3 composite video out or RGB out or Y/C out	SDAC-3165

Prices and specifications are subject to change without notice